

Wood Chipper GS73G

The smallest model has
many useful functions



Max. chipping dia.
7
cm

Max. capacity

1.5 m³/h

Fuel

2.2 L/h

Standard Screen

Loading Truck

Light truck

Max. output

7.0 HP

Weight

200 kg

30 mm

Hoisting

-

Basic performance

Easy maintenance

Rotor Cover



Hopper



No special devices required to open rotor upper unit or hopper. Designed for easy daily check and replacement of blades.

Automatic No Stress control

Electromagnetic clutch with large size brake



Newly introduced electromagnetic clutch with large size brake has not just achieved to prolong the lifetime of clutch but also greatly improved the feeding efficiency.

※Chipping efficiency has improved 1.5 times compare to its old model.

Safety design

Emergency stop button



Prevent feeding accidents by stopping engine with "Emergency Engine Stop Button".

Feeding operation



Easy to start and stop feeding with switch at hand.

Pressure prevention function



When in reverse, slight pressure on the brake lever halts the machine reducing the risk of accidents.

Feed roller release with FS set lever



Became easier to release the feed roller by simply pushing the FS lever if materials become clogged.

※ Patent pending for FS set lever

Option

Long high shooter



Suitable and convenient to discharge chips into a light truck or into a bulk bag.

※ Not available with screen.



Shredder knife



Chipping efficiency is increased and finer chips are produced.

Screen 10・20・40mm



※ Regular screen 30 mm

Chipping efficiency is increased and finer chips are produced.



Main Specifications

	Item	Description		Item	Description
Total	Product / Model	Wood Chipper / GS73G	Chipping	Blade	Chipper knife x2pcs / Counter knife x1pc
	L×W×H	1280×655×1075 mm		Infeed dimensions	335×230 mm
	Weight	200 kg		Drive system	Belt clutch, V belt
	Max. chipping dia.	70 mm (soft wood)		Feeding system	Mechanical drive feed roller system
	Max. capacity	1.5 m ³ /h (Regular screen 30mm)		Output typr	Air conveying system
Power	Engine	Mitsubishi GB221PN Gasoline Engine	Output	Output height	540mm
	Max. output	7.0 (5.1) ps(kw)		Output angle	Variable
	Fuel	Automobile unleaded gasoline		Drive	Steering type
	Fuel tank	3.6 L	Drive type		Self-propelled crawler type
	Fuel consumption	2.2 L/h	Speed		F1: 1.9 km/h, F2: 3.9 km/h R: 1.9 km/h
	Starting system	Recoil Starter			

* Specifications are subject to change without notice.