

Chip Wood • Leafy Branches • Straw and even Vegetables with **ohashi** Chippers

Mobile
Chippers

ES151GH

FEATURES

- * Maximum power in mobile, compact, light weight body
- * For composts, mulching, making pellets or bio-energy
- * Hydraulically powered automatic infeed rollers
- * Made in Japan - Japanese quality and reliability



Max. diameter

6"

Max. output

23

HP

Weight

1080

lb



Only 29" wide!



Leafy branches OK



No stress micro-computer



Able to load on a light truck or trailer

Wood Chipper ES151GH Basic performance

Max chipping dia. 6" (15 cm)

Wood



ES151GH can chip wood and leafy branches of 6" max. Leaves are also well processed. Chips can be used for composts, mulching, making pellets or bio-energy.

Leafy branches



Two Stage Process

Chipper knife



Turn logs into chips with the powerful 2 blade rotating chipper knife.

Shredder knives



Increase chipping efficiency
※ 8 pcs / unit

Fan forced Shooter

Dispatch chips into truck or flexi bag



Fan forced shooter dispatches chips fast and directly to a truck or a flexi bag.



Dispatch above or below

Shooter



Change the dispatch angle or direction at your convenience.

Low dispatch unit



When chipping in places where a shooter may cause obstructions, like an orchard, disable the shooter and dispatch chips from below.



Easy Maintenance

Rotor cover



Knife inspection and maintenance.

Hopper



Oil inspection and engine maintenance.

Blower cover



Fan blower inspection and maintenance.

Hour meter



Equipped with hour meter.

Fuel-saving mode

Efficient Feeding



The feed mode switch allows the user to match and optimize the feeding settings to the material being chipped.

Easy to load on truck

Loading and unloading



Self-propelled crawler and compact, light weight body enable you to load onto or unload from a truck easily.



Wood Chipper ES151GH Basic performance

Automatic No Stress Control

Hydraulic motor



An automatic hydraulic No Stress control system, communicates with the feed roller ensuring stable and efficient feeding of materials.

Micro computer



Micro-computer between the feed roller and engine reduces engine loading stress and prevents damage.

Safety Design

Feed roller safety bar



Allow users to stop the feed roller in an emergency and if necessary without using their hands.

Brake handle



The brake handle is gripped to transport the vehicle. When released the parking brake will be activated automatically.

Advanced functions

Feed switch



It is easy to take out any clogged materials with the reverse feeding by just turning the feed switch.

Hoisting



Reinforced robust body allows for stable hoisting while attaching rope to the machine at only one place!

Blowing power



Chip to the very back of a truck with greatly increased blower power.

Wide hopper



Wide hopper for easy feeding of thick leafy branches.

Chip Applications

Bedding



Compost




Pathways




Pellets



Mulching



Heat Water



Options

Flat blade <For chipping grass and bark>



Attach flat blade to the feed roller to avoid clogging on sharp edges.

* Grass containing more water, should be discharged via the low dispatch unit because chipped grass might clog up the shooter.



Flexi bag



Easy to collect chips and eliminate mess.

Vacuum collector



Processed chips are efficiently collected and packed without raising dust.

※Made in Murakoshi:MY-150XN

Recommended Options

Adjust the chip size

ES151GHB - Adjust the chip size



Choose the chip size to suit your needs with ES151GHB's Flow Controller. Allows you to speed up the infeed to produce larger chips or slow down to produce very small chips for pelletizing, bio-energy and fertilizer. Use in combination with screens.

※ES151GHB is equipped with flow controller and one more screen (5mm or 8mm holed) plus standard screen (30mm holed).

Flow controller




The processing speed is adjustable by turning the flow controller. Allows you to adjust the chip size.

Screen sizes - For uniform sized chips


30mm holed screen



8mm holed screen



5mm holed screen



To adjust chip size and to produce uniform sized chips just change the screen.

※Different hole sized screens can be made on request.

Chip sizes

30mm holed screen



8mm holed screen



5mm holed screen



Different chip sizes suit different purposes. Choose the hole size of screen based on your needs.

ES151GH / ES151GHB Specifications

Factor		Description	Factor		Description
Total	Product / Model name	Wood Chipper ES151GH/ES151GHB	Chipping	Feeding system	Automatic hydraulic No Stress control
	L × W × H	In use - 95 x 29 x 61.5" In transport - 71.5 x 29 x 63.5"		Drive system	Belt clutch, V belt
Power	Weight	1080 lb (490 kg)		Max.chipping dia.	6" (150 mm)
	Engine	Briggs & Stratton Vanguard V-Twin		Blade	Chipper knife 2pcs / Counter knife 1pc
	Max. output	23.0 HP / 17.1 kw		Shredder knife	8pcs
	Fuel	Unleaded gasoline	Drive	Infeed dimensions	6 x 8" (150 x 205 mm)
	Fuel tank	4 gal (15 L)		Starting System	Cell Starter
Output	Fuel consumption	1.7 gal (6.5 L) per hour.		Steering type	Side Cluth
	Output type	Fan forced shooter		Drive type	Self-propelled crawler type
	Height of shooter	61.5" (1560 mm)		Speed	F1 : 0.75 mph (1.2 km/h) F2 : 1.55 mph (2.5 km/h) R : 0.85 mph (1.4 km/h)
Output shooter angle		Variable in 270°			

*Specifications are subject to change without notice.



ohashi inc.

401 SAKIMURA CHIYODA KANZAKI
SAGA JAPAN 842-0065
JAPAN TEL +81-952-44-3135
E-MAIL global@ohashi-inc.com
WEB www.ohashi-inc.com